



2-PLY 2" x 12" (OR LVL)  
FRAMING FOR  
MECHANICAL SUPPORT

ELEVATOR CAR

ELEVATOR  
MECHANICAL

48  
FINISHED  
HOISTWAY

ADDITIONAL NOTES:

- GROUND FLOOR ORIENTATION SHOWN.
- HOISTWAY DOORS & FRAMES TO BE INSTALLED IN A 2" x 4" CONSTRUCTED WALL; AS REQUIRED TO COMPLY WITH THE 3" x 5" CODE RULE.
- HOISTWAY DOORS TO BE SOLID CORE (SUPPLIED BY OTHERS).
- MAX 1 IN. CLEARANCE BETWEEN ELEVATOR FLOOR AND ENTRY POINTS.

NOTES:

1. ALL DIMENSIONS ARE SPECIFIC TO HEI EQUIPMENT AND ELEVATOR CODES AND MUST BE MAINTAINED TO ENSURE PROPER INSTALLATION. NOTIFY HYBRID ELEVATOR ENGINEERING REGARDING ANY DIMENSIONAL CHANGES BEFORE PROCEEDING.
2. PROPOSED DIMENSIONAL LAYOUT ONLY.
3. ALLOWANCE FOR 1/2 IN. DRYWALL/PLYWOOD INCLUDED IN FINISHED HOISTWAY DIMENSIONS.
4. HOISTWAY WALLS **MUST BE FLUSH** WITH ELEVATOR PIT WALLS.

CONFIDENTIAL & PROPRIETARY  
THIS DOCUMENT CONTAINS INFORMATION  
PROPRIETARY TO HYBRID ELEVATOR INC.  
USE OR DISCLOSURE WITHOUT WRITTEN  
CONSENT OF HYBRID ELEVATOR IS  
EXPRESSLY FORBIDDEN.

ALL DIMENSIONS IN INCHES			
DRAWN CS	2019-07-18	TITLE HOISTWAY - 3' x 4', DUAL ENTRY [THRU], LEFT DRIVE STANDARD/LVL LUMBER	
APPROVED HYBRID ELEVATOR	2019-07-18	DRAWING # HEI-34-2LT	
SIZE B		DRAWING # HEI-34-2LT	REV 0
SCALE NTS		SHEET 1 OF 1	



**HYBRID ELEVATOR INC.**

MANUFACTURERS OF:  
ELEVATORS AND DISABILITY LIFTS

#16 - 634 LOUGHEED ROAD  
KELOWNA, BC V1X 7R8  
778-484-0064

**PROPRIETARY AND CONFIDENTIAL**