



- ADDITIONAL NOTES:
- GROUND FLOOR ORIENTATION SHOWN.
 - HOISTWAY DOORS & FRAMES TO BE INSTALLED IN A 2" x 4" CONSTRUCTED WALL; AS REQUIRED TO COMPLY WITH THE 3" x 5" CODE RULE.
 - HOISTWAY DOORS TO BE SOLID CORE (SUPPLIED BY OTHERS).
 - MAX 1 IN. CLEARANCE BETWEEN ELEVATOR FLOOR AND ENTRY POINTS.

- NOTES:
1. ALL DIMENSIONS ARE SPECIFIC TO HEI EQUIPMENT AND ELEVATOR CODES AND MUST BE MAINTAINED TO ENSURE PROPER INSTALLATION. NOTIFY HYBRID ELEVATOR ENGINEERING REGARDING ANY DIMENSIONAL CHANGES BEFORE PROCEEDING.
 2. PROPOSED DIMENSIONAL LAYOUT ONLY.
 3. ALLOWANCE FOR 1/2 IN. DRYWALL/PLYWOOD INCLUDED IN FINISHED HOISTWAY DIMENSIONS.
 4. HOISTWAY WALLS ON LANDING SIDES MUST BE PLUMB.

CONFIDENTIAL & PROPRIETARY
 THIS DOCUMENT CONTAINS INFORMATION
 PROPRIETARY TO HYBRID ELEVATOR INC.
 USE OR DISCLOSURE WITHOUT WRITTEN
 CONSENT OF HYBRID ELEVATOR IS
 EXPRESSLY FORBIDDEN.

ALL DIMENSIONS IN INCHES	
DRAWN CS	2019-07-18
APPROVED HYBRID ELEVATOR	2019-07-18
 3rd ANGLE PROJECTION	



HYBRID ELEVATOR INC.
 MANUFACTURERS OF:
 ELEVATORS AND DISABILITY LIFTS

#16 - 634 LOUGHEED ROAD
 KELOWNA, BC V1X 7R8
 778-484-0064

PROPRIETARY AND CONFIDENTIAL

TITLE HOISTWAY - 3' x 4', DUAL [THRU] ENTRY, RT DRIVE STANDARD/LVL LUMBER	
SIZE B	DRAWING # HEI-34-2RT
SCALE NTS	REV 0
SHEET 1 OF 1	