



- ADDITIONAL NOTES:
- GROUND FLOOR ORIENTATION SHOWN.
  - HOISTWAY DOORS & FRAMES TO BE INSTALLED IN A 2" x 4" CONSTRUCTED WALL; AS REQUIRED TO COMPLY WITH THE 3" x 5" CODE RULE.
  - HOISTWAY DOORS TO BE SOLID CORE (SUPPLIED BY OTHERS).
  - MAX 1 IN. CLEARANCE BETWEEN ELEVATOR FLOOR AND ENTRY POINTS.

- NOTES:
1. ALL DIMENSIONS ARE SPECIFIC TO HEI EQUIPMENT AND ELEVATOR CODES AND MUST BE MAINTAINED TO ENSURE PROPER INSTALLATION. NOTIFY HYBRID ELEVATOR ENGINEERING REGARDING ANY DIMENSIONAL CHANGES BEFORE PROCEEDING.
  2. PROPOSED DIMENSIONAL LAYOUT ONLY.
  3. ALLOWANCE FOR 1/2 IN. DRYWALL/PLYWOOD INCLUDED IN FINISHED HOISTWAY DIMENSIONS. FINISHED HOISTWAY WALLS **MUST BE FLUSH** WITH ELEVATOR PIT WALLS.
  4. HOISTWAY WALLS ON LANDING SIDES MUST BE PLUMB.

CONFIDENTIAL & PROPRIETARY  
 THIS DOCUMENT CONTAINS INFORMATION  
 PROPRIETARY TO HYBRID ELEVATOR INC.  
 USE OR DISCLOSURE WITHOUT WRITTEN  
 CONSENT OF HYBRID ELEVATOR IS  
 EXPRESSLY FORBIDDEN.

ALL DIMENSIONS IN INCHES	
DRAWN CS	2019-07-18
APPROVED HYBRID ELEVATOR	2019-07-18
 3rd ANGLE PROJECTION	



**HYBRID ELEVATOR INC.**  
 MANUFACTURERS OF:  
 ELEVATORS AND DISABILITY LIFTS

#16 - 634 LOUGHEED ROAD  
 KELOWNA, BC V1X 7R8  
 778-484-0064

**PROPRIETARY AND CONFIDENTIAL**

TITLE HOISTWAY: 4' x 4', DUAL ENTRY, RIGHT DRIVE STANDARD/LVL LUMBER		REV 0
SIZE B	DRAWING # HEI-44-4RT	
SCALE NTS	SHEET 1 OF 1	