



2-PLY 2" x 12" (OR LVL)
FRAMING FOR
MECHANICAL SUPPORT

ELEVATOR
MECHANICAL

ELEVATOR CAR

61.5
FINISHED
HOISTWAY

- ADDITIONAL NOTES:
- GROUND FLOOR ORIENTATION SHOWN.
 - HOISTWAY DOORS & FRAMES TO BE INSTALLED IN A 2" x 4" CONSTRUCTED WALL; AS REQUIRED TO COMPLY WITH THE 3" x 5" CODE RULE.
 - HOISTWAY DOORS TO BE SOLID CORE (SUPPLIED BY OTHERS).
 - MAX 1 IN. CLEARANCE BETWEEN ELEVATOR FLOOR AND ENTRY POINTS.

- NOTES:
1. ALL DIMENSIONS ARE SPECIFIC TO HEI EQUIPMENT AND ELEVATOR CODES AND MUST BE MAINTAINED TO ENSURE PROPER INSTALLATION. NOTIFY HYBRID ELEVATOR ENGINEERING REGARDING ANY DIMENSIONAL CHANGES BEFORE PROCEEDING.
 2. PROPOSED DIMENSIONAL LAYOUT ONLY.
 3. ALLOWANCE FOR 1/2 IN. DRYWALL/PLYWOOD INCLUDED IN FINISHED HOISTWAY DIMENSIONS.
 4. HOISTWAY WALLS ON LANDING SIDES MUST BE PLUMB.

CONFIDENTIAL & PROPRIETARY
THIS DOCUMENT CONTAINS INFORMATION
PROPRIETARY TO HYBRID ELEVATOR INC.
USE OR DISCLOSURE WITHOUT WRITTEN
CONSENT OF HYBRID ELEVATOR IS
EXPRESSLY FORBIDDEN.



HYBRID ELEVATOR INC.
MANUFACTURERS OF:
ELEVATORS AND DISABILITY LIFTS

#16 - 634 LOUGHEED ROAD
KELOWNA, BC V1X 7R8
778-484-0064

PROPRIETARY AND CONFIDENTIAL

ALL DIMENSIONS IN INCHES			
DRAWN CS	2019-07-19	TITLE HOISTWAY: 4' x 5', SINGLE ENTRY, LEFT DRIVE STANDARD/LVL LUMBER	
APPROVED HYBRID ELEVATOR	2019-07-19	SIZE B	DRAWING # HEI-45-1LT
3rd ANGLE PROJECTION		SCALE NTS	REV 0
			SHEET 1 OF 1