



2-PLY 2" x 12" (OR LVL)  
FRAMING FOR  
MECHANICAL SUPPORT

- ADDITIONAL NOTES:
- GROUND FLOOR ORIENTATION SHOWN.
  - HOISTWAY DOORS & FRAMES TO BE INSTALLED IN A 2" x 4" CONSTRUCTED WALL; AS REQUIRED TO COMPLY WITH THE 3" x 5" CODE RULE.
  - HOISTWAY DOORS TO BE SOLID CORE (SUPPLIED BY OTHERS).
  - MAX 1 IN. CLEARANCE BETWEEN ELEVATOR FLOOR AND ENTRY POINTS.

- NOTES:
1. ALL DIMENSIONS ARE SPECIFIC TO HEI EQUIPMENT AND ELEVATOR CODES AND MUST BE MAINTAINED TO ENSURE PROPER INSTALLATION. NOTIFY HYBRID ELEVATOR ENGINEERING REGARDING ANY DIMENSIONAL CHANGES BEFORE PROCEEDING.
  2. PROPOSED DIMENSIONAL LAYOUT ONLY.
  3. ALLOWANCE FOR 1/2 IN. DRYWALL/PLYWOOD INCLUDED IN FINISHED HOISTWAY DIMENSIONS.
  4. HOISTWAY WALLS ON LANDING SIDES MUST BE PLUMB.

CONFIDENTIAL & PROPRIETARY  
THIS DOCUMENT CONTAINS INFORMATION  
PROPRIETARY TO HYBRID ELEVATOR INC.  
USE OR DISCLOSURE WITHOUT WRITTEN  
CONSENT OF HYBRID ELEVATOR IS  
EXPRESSLY FORBIDDEN.



**HYBRID ELEVATOR INC.**  
MANUFACTURERS OF:  
ELEVATORS AND DISABILITY LIFTS

#16 - 634 LOUGHEED ROAD  
KELOWNA, BC V1X 7R8  
778-484-0064

**PROPRIETARY AND CONFIDENTIAL**

ALL DIMENSIONS IN INCHES			
DRAWN CS	2019-07-17	TITLE HOISTWAY: 4' x 4', SINGLE ENTRY, RIGHT DRIVE STANDARD/LVL	
APPROVED HYBRID ELEVATOR	2019-07-18	SIZE B	DRAWING # HEI-44-1RT
3rd ANGLE PROJECTION		SCALE NTS	REV 0
		SHEET 1 OF 1	