


NOMINAL CAR SIZE: 4 x 5
NOMINAL PLATFORM AREA: 19.3 SQ. FT./1.79 SQ. M
NET PLATFORM AREA: 16.6 SQ. FT./1.54 SQ. M



CARRIAGE GATE OPTION:
SUPPLIER: GOOD GATE
OPENING WIDTH: 36 IN.
AVAILABLE HEIGHTS:
80/84/96 IN.
LH- & RH-OPENING
(LH & RH OPTIONS SHOWN)



NOTES:

1. ALL DIMENSIONS ARE SPECIFIC TO HEI EQUIPMENT AND ELEVATOR CODES AND MUST BE MAINTAINED TO ENSURE PROPER INSTALLATION. NOTIFY HYBRID ELEVATOR ENGINEERING REGARDING ANY DIMENSIONAL CHANGES BEFORE PROCEEDING.
2. PROPOSED DIMENSIONAL LAYOUT ONLY. GROUND FLOOR ORIENTATION SHOWN.
3. **ALLOWANCE FOR 1/2 IN. DRYWALL/PLYWOOD INCLUDED IN FINISHED HOISTWAY DIMENSIONS. FINISHED HOISTWAY WALLS MUST BE FLUSH WITH ELEVATOR PIT WALLS.**
4. **HOISTWAY WALL ON LANDING SIDE MUST BE PLUMB.**

CONFIDENTIAL & PROPRIETARY
THIS DOCUMENT CONTAINS INFORMATION
PROPRIETARY TO HYBRID ELEVATOR INC.
USE OR DISCLOSURE WITHOUT WRITTEN
CONSENT OF HYBRID ELEVATOR IS
EXPRESSLY FORBIDDEN.

| | | | |
|--|------------|--|---------------------------------|
| ALL DIMENSIONS IN INCHES | |  778-484-0064 PROPRIETARY AND CONFIDENTIAL | |
| DRAWN CAS | 2025-04-29 | TITLE HOISTWAY: 4' x 5', DUAL ENTRY, LEFT DRIVE STD/LVL LUMBER, CARRIAGE GATES | |
| APPROVED HYBRID ELEVATOR | | | |
| | | SIZE B | DRAWING # 2025-HEI-45-2LT_GG |
|  3rd ANGLE PROJECTION | | SCALE NTS | REV |
| | | | SHEET 1 OF 1 |

ADDITIONAL NOTES

- HOISTWAY DOORS TO BE INSTALLED NO MORE THAN 0.75 IN. FROM THE HOISTWAY WALL; AS REQUIRED FOR THE 3/4 x 4 CODE COMPLIANCE.
- HOISTWAY DOORS TO BE SOLID CORE (SUPPLIED BY OTHERS).
- MAX 1 IN. CLEARANCE BETWEEN ELEVATOR FLOOR AND ENTRY POINTS.